



# FRAC-IN

*Enabling in situ soil remediation on low-permeability sites through hydraulic/pneumatic fracturing (FRAC-IN)*

Axelle Mineur (ABO-Group – Belgium)





# Table of contents




- Context
  - Water-soil interactions
  - Lack of interactions & in situ remediation
- LIFE FRAC-IN
  - Aim & applications
  - Technology
  - Results
- Animation of the technology



# Context: Water-soil interactions

- Water soil interface = gradient of permeability
- Chlorinated solvents, mineral oils and other pollutants tend to be sorbed on the soil
  - First need to desorb them
  - Before you can treat them




(5.7: Soil-Water Relations, by Anna R. Schwyter & Karen L. Vaughan, University of Wyoming)



# Context: Lack of interactions & in situ remediation


- Remediation
  - Requires contact between
    - Remediation agents
    - Contaminants
- Remediation agents => move through water to reach the contamination
- Poor permeability: reduces efficiency of in situ remediation (chem, bio)



# Context: Lack of interactions & in situ remediation


- Remediation
  - Requires contact between
    - Remediation agents
    - Contaminants
- Remediation agents => move through water to reach the contamination
- Poor permeability: reduces efficiency of in situ remediation (chem, bio)

=> artificial porosity!





# LIFE FRAC-IN



- Duration: 2022-01-01 – 2025-12-31
- Budget: 1.786.230 €
- Partners
  - DEKONTA a.s.
  - ABO NV
- 7 sites => 3 in CZ and 4 in BE



- Enable in situ remediation using
  - Biological reagents
  - Chemical reagents
- Poorly permeable soils
- Varied pollutants
  - Mineral oils, chlorinated solvents, HM, pesticides etc.

⇒ Artificial porosity







# LIFE FRAC-IN: Technology





A


B

C


D

4 injection lines

1 injection probe



FRAC-IN




4 injection lines

1 injection probe



FRAC-IN



Compressor


4 injection lines

Circulation tank

1 injection probe



FRAC-IN



Mixing tank

Circulation tank

1 injection probe


Compressor

4 injection lines

Reagents (optional)



FRAC-IN



Mixing tank

Circulation tank

1 injection probe

4 injection lines

Reagents (optional)

Rinsing



FRAC-IN



Water

Circulation

Mixing tank

Reagents

Valve control station

# Results demonstration - Duchcov site

- Low permeability site in Czechia
  - Historical contamination
  - Mixture of Cr6+ & chlorinated solvents
- Guar gum solution
  - With coarse sand, milled cast iron, mZVI and nZVI
  - Combined with glycerol as a remediation agent
- 3 injection campaigns with monitoring & intermediate surveys  
=> In total 106 FRAC-IN injection points





# Results demonstration - Duchcov site



- Cr6+: quickly reduced within weeks after the injections
- Chlorinated solvents: gradually degraded due to the extreme activity of degrading bacteria combined with the abiotic reduction triggered by the injections


=> The remediation was completed successfully







# Animation of the technology





# FRAC-IN

*Enabling in situ soil remediation on low-permeability sites through hydraulic/pneumatic fracturing (FRAC-IN)*

Axelle Mineur (ABO-Group – Belgium)

[axelle.mineur@abo-group.eu](mailto:axelle.mineur@abo-group.eu)



**Co-funded by  
the European Union**

